



## Premium 2-Channel Tone- and Speech Audiometer

Air- & Bone-Conduction, Free Field,  
additional connector for Insert-Phone or HF-Headset  
Standard frequency range 125 Hz to 12.5 kHz  
**HD-Speech Module for localized Speech Testing**

- Rip CD's to Harddisk
- Edit Track Information (Start/End/Text of Words in Track)
- Edit rules for adaptive Speech Tests
- Present Speech Tests with single word stepping

## Extensiv Set of Special Tests

Tinnitus Marking, Tinnitus Masking, SISI, Fowler, Langenbeck (Tone in Noise), Lüscher, Stenger

## Extensive Print Form Management

- Multiple predefined Print Forms included
- Editor for customization of Print Forms included
- Print Forms incl. Check Boxes, Text Fields etc.
- Infilled Print Forms can be stored in Database

## Pure Software Control, seamless IT Integration

- Easy text based interface for integration in Data Management Software (GDT)
- Full XML Export of Measurement for integration in e.g. Innoforce Diagnostic Manager

## Import Measurements from other Devices

Tympanometer Interacoustics AT22, At235  
M.R.S. r26m, r36m  
Inventis Flute

## Integrated Patient Communication

Talk Back & Talk Forward for connection to Sound Proof Booths

## Integrated Galvanic Isolation

No isolation transformer / medical PC required

## Integrated Free Field Speaker Amplifier (CA 450)